




**CONTI-AIR®**  
BLANKET TECHNOLOGY

**CONTI-AIR® EBONY+**  
Sheetfed All-Purpose Blanket

# CONTI-AIR® EBONY+



Coldset



Heatset



Sheetfed



Packaging



Metaldeco

## Das weiterentwickelte EBONY, mit spezieller Karkasse und 2 integrierten kompressiblen Schichten.

- › Beständig gegen konventionelle, Hybrid- und UV-Farben sowie die dazugehörigen Waschmittel
- › Verringerter Papierstaubaufbau
- › Unempfindlich gegen Kanteneinschneiden bei Formatwechseln
- › Sehr gutes Papierfreigabeverhalten gerade bei empfindlichen Bedruckstoffen
- › Sehr gutes Spann- und geringes Dehnverhalten

## The further developed EBONY, with special carcass design and 2 integrated compressible layers.

- › Resistant to conventional, hybrid and UV inks and their appropriate washing agents
- › Reduced paper dust build-up
- › Less paper edge marking through different format sizes
- › Very good quick release behavior especially in the case of sensitive substrates
- › Very good tensioning and low elongation


### Richtwerte / Guiding Value

|                                                                                |                                  | Norm / Standard    |
|--------------------------------------------------------------------------------|----------------------------------|--------------------|
| <b>Farbe:</b><br><b>Color:</b>                                                 | schwarz<br>black                 |                    |
| <b>Oberfläche:</b><br><b>Surface:</b>                                          | feinstgeschliffen<br>microground |                    |
| <b>Härte Deckgummi:</b><br><b>Hardness of face compound:</b>                   | 55 Shore A                       | DIN ISO 48-4*/**   |
| <b>Kompressibilität bei 1.350 kPa:</b><br><b>Compressibility at 1.350 kPa:</b> | 0,220 mm                         | R_05_10AA3119*     |
| <b>Nennstärke:</b><br><b>Thickness:</b>                                        | 1,96 mm +/-0,02 mm               | DIN EN ISO 2286-3* |


\* In Anlehnung an die gegebene Norm durchgeführt. Bitte beachten Sie, dass die Anzahl der getesteten Stichproben variieren kann.  
Performed in accordance with the given standard. Please note that the number of samples tested may differ.

\*\* Die ausgewiesene Härte für das Deckplattengummi kann nur an Prüfkörpern die der Norm entsprechen gemessen werden.  
The specified hardness of the cover compound can only be measured using test samples according to the standard. It is not possible to measure the hardness directly on the product itself.

Unsere Drucktücher verfügen über eine spezielle CONTI-AIR® kompressible Schicht geschlossener Mikrozellen mit Überdruck.



Our printing blankets have a special CONTI-AIR® compressible layer of overpressured microcells.



conventional

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2020 Continental AG, Hanover. All rights reserved.